

2610



The Tally Dascom 2610 is a highly featured, reliable and stylish machine. Performance and workload, ergonomics, maintainability, excellent price – everything has been incorporated to ensure it is the only acceptable choice for the customer.

Continuous and cut forms are fed at the front for quick and easy loading. This ensures a straight path for the forms resulting in reliable paper transportation, even on 7-part stock. Loading paper is easier. The operator does not have to

Highlights at a glance:

- Print speeds **up to 680 cps**
- **20,000 pages per month** workload
- 136 columns
- 24 pin print head produces excellent print quality
- **Straight through paper path** for easy forms loading
- Ethernet, parallel and USB interfaces

User intervention is kept to a minimum with a suite of features designed to ensure the products run at optimum reliability and performance.

The product is at home in the computer room, data processing room, or in the office. An unobtrusive 52 dBA acoustic rating results in a printer, which is half as quiet, compared with many competitive models.

Intelligent Mail Barcode - be sure your printer has this important feature

The US Postal Service new bar code standard



Configurations:

- **2610** Standard

2610

Print Speed	680 cps (Fastest Draft); 500 cps (HS-Draft), 333 cps (Draft), 111 cps (LQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Print Head Life	500 million dots per wire
Memory	256 kB
Standard Connectivity	Parallel (Bi-directional), USB 2.0 and Ethernet (10/100 BaseT)
Optional Connectivity	Serial RS-232
Standard Emulation	IBM ProPrinter XL24, Epson ESC/P2, MTPL + Barcode + LCP
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printing
Consumable	Ribbon: 15 million characters
Standard Paper Handling	One tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front off
Optional Paper Handling	Additional push tractor (rear),
Number of Copies	Push tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Cut sheet: 1 original + 5 copies
Paper Type	Cut sheets, continuous forms, multi-part forms
Paper Weight	60-120 g/m ²
Paper Size	Width: 76 to 420 mm, 3.0 to 16.5 in; Length: 76 to 599 mm, 3.0 to 23.6 in
Physical Weight	10.6 kg, 23.3 lbs
Physical Size	600 x 265 x 200 mm, 23.6 x 10.4 x 7.9 in (W x D x H)
Acoustic	52 dB(A)
Power Voltage	100 - 240 V wide range auto-sensing
Power Consumption	40 Watt Printing; <10 W Sleep Mode
Temperature	+10° to +40° C; 10% to 85% humidity
Workload	20,000 pages per month
MTBF	15,000 hours
Drivers	Windows 2000/XP/Vista/7/8/10 and Server 2003/2008; SAP
Warranty	One year return to depot

DASCOM Americas

34 Lakeview Ct.

Verona, VA 24482

Phone 877-434-1377 – Fax: 540-242-7221

www.dascomamericas.com

SERIAL MATRIX PRINTERS

MOBILE PRINTERS

FLATBED PRINTERS

THERMAL PRINTERS