

T2380



Tally

“Unsurpassed excellence”. That defines the rugged high powered T2380 printer. Built to leave a lasting impression on your productivity, this high speed workhorse exemplifies what rugged durability is all about. With its advanced 24-pin print head, the 2380 is engineered to perform at a blistering pace even in the harshest of operating environments. You’re assured of top-shelf performance, crisp, clear and reliable print quality and a machine you can count on when your performance is what counts.

Low running costs and durability in the harshest of print environments make these products excellent value for money.

Highlights at a glance:

- Full range of automatic features to minimize user intervention
- Ideal for ‘On-Demand’ and ‘Batch’ applications with zero tear for no wasted forms
- Straight through paper path for easy forms loading
- Parallel and Ethernet (10/100BaseT) standard.
- Optional Interfaces: RS232 Serial; Coax/Twinax; Ethernet IPDS
- Compatible with a wide range of operating systems including Windows, UNIX, DOS, SAP R3 and legacy systems

These products are well matched to Microsoft Windows applications, and highly compatible with other host operation environments including legacy systems.

Fully automated operation, coupled with the ‘straight through’ paper path, allows ease of use and virtually eliminates errors caused by user intervention.

Available Configuration:

- **T2380** Standard Product
- **T2380 2T** with additional rear tractor

T2380

Print Speed	1.000 cps (Fastest Draft); 800 cps (Draft), 222 cps (NLQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Throughput (ECMA 132)	625 pages per hour
Character Density	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	750 million strokes per pin
Standard Memory	128 kB
Standard Connectivity	Parallel (Bi-directional) and Ethernet 10/1q00 BaseT
Optional Connectivity	RS-232 Serial, Ethernet with SCS or IPDS, Coax/Twinax with SCS or IPDS
Standard Emulation	IBM ProPrinter XL24, Epson LQ (ESC P/2), MTPL + Barcode + LCP, Genicom ANSI
Optional Emulation	PCL 3 (Rugged Writer), IGP/PGL, Code V, MT660, Printronix P6000, HP2564C
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and scaleable LCP
Consumables	Ribbon: 20 million characters
Standard Paper Handling	Push tractor for continuous paper with straight paper path, tear off and park position
Optional Paper Handling	Additional push tractor (front), Automatic cutting device
Number of Copies	Push tractor front: 1 original + 5 copies Push tractor rear: 1 original + 3 copies (2T version)
Paper Type	Continuous forms, multi-part forms
Paper Weight	60-120 g/m ²
Paper Size	Width: 3" to 16.5"; Length: 3" to 22"
Physical Weight	19 kg
Physical Size	24.5" x 17" x 11" mm (W x D x H)
Acoustic	59 dB(A)
Power Voltage	120 V or 230 V (selectable)
Power Consumption	70 Watt Printing; 18 W Power-Save
Temperature	+10° to +35° C; 20% to 80% humidity (not condensing)
Workload	50.000 pages per month
MTBF	12.500 hours
Warranty	90 days on-site warranty
Drivers	Windows 2000/XP/Vista/7/10 and Server 2003/2008; SAP
Note	For OCR applications it is recommended that your readers are tested. Paper is a highly variable medium and should be tested prior to purchase.

DASCOM Americas Corporation

34 Lakeview Ct.
Verona, VA
USA 24482
Tel: 877 434 1377
www.dascomamericas.com

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 