

SOLID 45ET

Ideal for:

- Stickers, labels and tags
- Workflow documents
- Real-time or batch processing
- Top sheet printing

HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- Fast interruption-free printing or two formats with optional Dual Tractor system
- Completely trouble-free paper handling
- First page after just 2 seconds
- Up to 45 pages per minute
- SAP and AS/400 compatible through PCL5 + JetCAPS as well as LAN-IPDS
- Compatible with standard laser printers

MAXIMUM PERFORMANCE FOR SMOOTH PRODUCTION AND LOGISTICS PROCESSES



SOLID 45ET

The SOLID 45ET is a robust 8-inch production thermal printer, designed for toughest demands. Its sophisticated paper tractor feed system is constructed for highest functional reliability and for secure, trouble-free paper feeds at all times. PCL5 ensures compatibility with all standard laser printers and connection to SAP. The rapid start-up time, fast printing speed and reliable paper feed at all times predestine the SOLID 45ET for smooth integration in demanding logistics and production processes. The optional 'Dual tractor' system allows for fast, interruption-free printing – or for printing on two different media types.

Print Engine

Print technology	Thermal transfer/direct thermal harmonic (history-controlled near-edge print head) MPC 5.3 with Intel XScale PXA 255
Controller	(400 MHz RISC processor)
Print speed	up to 45 pages/min
Print resolution	300 dpi x 300 dpi
Lifetime print head	Transfer: up to 50,000 m
Power supply	110 / 240V autoselect
Power consumption	3.2 A
Dimensions (WxDxH)	17.7 in x 19.3 in x 12 in / 450mm x 490mm x 305 mm
Weight	57 lbs / 26 kg
Environment temperature	41 - 95°F / 5 - 35°C
Relative humidity	45 - 75 % (rel., non-condensing)
Interfaces	Serial: USB, RS232, RS422 Parallel: IEEE 1284 LAN, Ethernet-Interface 10/100 MBit, bi-directional (TCP/IP) RAM: 64 MB
Memory	Flash: 16 MB

MPC 5.3 High-End Print-Controller

Emulations

MICROPLEX IDOL, HP-PCL5/ HPGL, AGFA Reno, LN03+, BULL-MP6090, Datamax (FGL), Etimark MP-1220, TEC Bx72, TEC B6xx, LDC, ZPL II, EPL2, UBI Fingerprint, IER Command, Godex EZPL, Diablo 630, IBM Pro-printer, Epson FX-80, MT-600/MT40, IDS, ANSI Genicom, TIFF, HP Designjet, XML (SAP RFID), CUPS Raster

Optional Emulations

μ-Postscript, CODE-V (Magnum), XEROX XES, KODESCRIPT+, Prescribe/PSB 2, IGP-10, Datamax Labelpoint, IPDS, AEA, AFP, RFM (more emulations on request)

Barcodes

QR Code, EAN 8, 13, 128, add on, 2/5 3-stroke Datalogic, 2/5 3-stroke Matrix, Codabar, PDF 417, Royalbar, Planet, Jetcaps (HP/SAP), Code 39, 128 MSI, UPC A, E, Postnet, KIX, USPS One Code

Optional Barcodes

USD5, Aztec-Code, UPS-Maxicode, Datamatrix (more barcodes on request)

Additional functions

Intelligent barcode generation on-the-fly in the printer

Format splitting

in several subformats by command

Ribbon Save Mode

active from 12 mm unprinted length, to save ribbon

Optional functions

Integrated form management

up to 12 MB flash for forms and fonts inside the printer

Status-Out

gives notice of each correctly printed page via interface


SPS-Control (EMBEDDED INTELLIGENCE - Enabling two-way communication between printer and a PLC)

integration of the printer into production lines is possible, controlled by SPS-interface.



Printable Media

Size	
Width	110 - 240 mm width printable width 213 mm
Weight	max. 120 g/m ² at suitable quality up to 160 g/m ²
Paper thickness	0.2 - 0.9 mm
Thermal transfer ribbon	roll diameter max. 90 mm
core diameter	1 inch (25.4 mm)
ribbon length	max. 600 m
Coated side	inside
Ribbon width	40 - 217 mm



Paper Path

Input

Continuous
internal from roll, external, e.g. fanfold

Optional

dual tractor version as factory option (SOLID 45ET-2)
sensor for backside marking

Optional

Single / Job cutter

The brand names referred to are the registered trademarks of the respective companies. All figures and details in italics and highlighted in color are optional. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 08.05.2017

Microplex Printware
100 Northfield rd Bedford, OH 44146 USA
phone 440-374-2424 | fax 440-374-2422

