


Tally 4347-i06n/w multiform printers



IBM Compatible Matrix Printer Solutions Built to Last

The Tally Dascom 4347-i06 is a highly featured, reliable and stylish machine. Performance and workload, ergo-nomics, maintainability, excellent price – everything has been incorporated to ensure it is the only acceptable choice for the customer.

Continuous and cut forms are fed at the front for quick and easy loading. This ensures a straight path for the forms resulting in reliable paper transportation, even on 6-part stock. Loading paper is easier. The operator does not have to fumble over or around the printer to gain access to rear located tractors.

Highlights at a glance:

- Print speeds up to 680 cps
- 20,000 pages per month workload
- 80 and 136 column versions
- 24 pin print head produces excellent print quality
- Straight through paper path for easy forms loading
- Ethernet, parallel and USB interfaces standard
- LCD Display for easy operation
- Internal ethernet for easy system connections
- Intelligent Mail Barcode Support

The Right Connectivity & Easy to Operate

User intervention is kept to a minimum with a suite of features designed to ensure the products run at optimum reliability and performance.

The product is at home in the computer room, data processing room, or in the office. An unobtrusive 52 dBA acoustic rating results in a printer, which is 50% quieter, compared with many competitive models.

Intelligent Mail Barcode -The US Postal Service new bar code standard requires this capability to take advantage of the best rates available.



Sample Intelligent Mail Barcode

Configurations:

4347-i06n - 80 col

4347-i06w - 136 col

Industrial



SOLUTIONS FOR BUSINESS PRINTING

Tally 4347-i06 multiform printer

Print Speed	680 cps (Fastest Draft); 500 cps (HS-Draft), 333 cps (Draft), 111 cps (LQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	500 million dots per wire
Memory	128 kB
Standard Connectivity	Parallel (Bi-directional), USB 2.0 and Ethernet (10/100 BaseT)
Optional Connectivity	Serial RS-232
Standard Emulation	IBM ProPrinter XL24, Epson ESC/P2, MTPL + Barcode + LCP
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printing
Consumable	Ribbon: 8 million characters/-i06w 6 million/-i06n
Standard Paper Handling	One tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, Auto Tear Off
Optional Paper Handling	Additional push tractor (rear)
Number of Copies	Push tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 1 copy; Cut sheet: 1 original + 5 copies
Paper Type	Cut sheets, continuous forms, multi-part forms
Paper Weight	60-120 g/m ²
Paper Size	-i06n Width: 76 to 278 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 in -i06w Width: 76 to 420 mm, 3.0 to 16.5 in; Length: 76 to 599 mm, 3.0 to 23.6 in
Physical Weight	i06n -8.6 kg, 18.9 lbs, i06w - 10,6 kg, 23.3 lbs
Physical Size	i06n - 458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H) i06w -600 x 265 x 200 mm, 23.6 x 10.4 x 7.9 in (W x D x H)
Acoustic	52 dB(A)
Power Voltage	100 - 240 V wide range auto-sensing
Power Consumption	40 Watt Printing; <10 W Sleep Mode
Temperature	+10° to +40° C; 10% to 85% humidity
Workload	20.000 pages per month
MTBF	20.000 hours
Drivers	Windows 2000/XP/Vista/7/8 /10 and Server 2003/2008; SAP

Note: For OCR applications it is recommended that your readers are tested with print samples supplied by DASCOM prior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operating conditions.

On-site warranty service requires location in Dascom's service coverage areas.

